



FLOORSAFE PEEL & STICK TACTILE PADS

Floorsafe 300mm x 300mm x 7mm self-stick tactile pads meet the requirements of the Australian standard AS/NZS4586:2004.

Conforms to the Disability Discrimination Act (DDA) easy with no fuss.

Manufactured to Australian & New Zealand standards 1428.4: 2002 Table 1

Slip tested in accordance with AS/NZS: 4586:2004 Mean tested BPN 41 Class X Ramp test result R10

Meets the classification Y BPN 25-34 according to AS/NZS: 4586:2004

FLEXIBLE & EASY TO INSTALL

Floorsafe Peel & Stick Tactile pads are fast & easy to install.

No down time because they can be walked on immediately.

Available in 3 colours black, yellow & terracotta both in warning/hazardous & directional.

Suitable for concrete, timber, pavers, ceramic, stone & bitumen.

ENHANCED BONDING TECHNIQUE

A special primer is supplied with the pads

The primer is a white liquid solution that is applied to the surface and left to dry for 10 – 15 minutes before applying the self-stick pads

UV STABLE

Manufactured from a strong durable Polyurethane these pads are flexible, hard wearing & long lasting Provides optimum UV stability and wear resistance with no colour fade after 48 months

Density	1390 kg/m ³
Young's modulus (E)	2900-3300 MPa
Tensile strength (σ_t)	50-80MPa
Elongation at break	20-40%
Notch test	2-5 kJ/m ²
Heat transfer coefficient (λ)	0.16 W/(m·K)
Melting point	250°C
Effective heat of combustion	17.95 MJ/kg
Specific heat (c)	0.9 kJ/(kg·K)
Size	300mm x 300mm
Thickness	7mm base to top of Tactile
Colours available	Black, yellow & terracotta
Warranty	10 Years under normal conditions