

ANTI-SLIP SELF-ADHESIVE TAPE



Introduction

The Floorsafe Anti-slip self-adhesive grip tape has the highest possible safety rating and is particularly suitable for both internal & external applications. Used extensively on steps, stairways and ramps the product exceeds the requirements of the Australia/New Zealand Standards for anti-slip AS4586:2004, Slip resistance classification of new pedestrian surface materials and the National Construction code.

Compliance

The Floorsafe Anti-slip self-adhesive tape is available in various colours to meet the minimum depth and luminance contrast requirements of the National Construction Code 3.2 and the Australian/New Zealand Standards AS1428 – 2009 Design for access and mobility, Part.1 (a minimum 50mm width tape must be used).

Application

- To be applied to surface where there may be a safety hazard due to slipperiness either in or outdoors
- Any non-porous surface void of dust, oil, water and other contaminants

Primer

- Aids adhesion using Floorsafe Australia Surface Primer

Technical Data

- Aluminium Oxide
- Grit Grade: #36 or #60
- Holding Medium: Solvent Acrylic Adhesive
- Tensile Strength: 7kgf/25mm
- Elongation at break: 80%
- Application Temp: -5c to 50c
- Resistance to Water: 12 months
- Resistance to Grease: 8 months
- Staining of Adhesive: No evidence of migration

Colours available in #60 Grade Grit

- Black, Yellow, White, Red, Green, Grey, Yellow/Black Hazard, Clear Non Abrasive, Clear Heavy Duty, Glow in the Dark, Black with Glow Strip, Yellow/Black Hazard Glow in the Dark

Colours available in #36 Grade Grit

- Yellow and Black

Sizes

- Available in 12mm Black, Yellow & Luminous and 25mm to 300mm in most colours (#60 Grade Grit)
- Available in 50mm Yellow & Black (#36 Grade Grit)