



Tactile Ground Surface Indicator	
<b>Code</b>	T023
<b>Type</b>	Warning tactile
<b>Material</b>	316 Stainless steel and polyurethane material
<b>Dimensions</b>	Outer Dia 35mm x top diameter 25mm x Height 4.5mm <b>Stem: 26mm</b>
<b>Slip Rating</b>	R12
Features	
Outer circle made with polyurethane material with a stainless steel insert (unsaturated polyester incorporating polyurethane rubber)	
Suitable for carpet	
Complies with Australian/New Zealand Standard 1428.1 2009	
Complies with Australian/New Zealand Standard 1428.4.1 2009 (TGSI)	
Complies with the NCC Section D3.8	
8 Year warranty	
Corrosion Proof	
Luminance Contrast	
The Building Code of Australian/New Zealand and the AS/NZS 1428.4.1 require a minimum luminance contrast of 30%. Guide lines are as follows:	
<ul style="list-style-type: none"> <li>— Integrated tactile indicators – not less than 30% across the entire area</li> <li>— Discrete (individual) tactile indicators – not less than 45%</li> <li>— Where Discrete tactile indicators are constructed of two colours or materials the raised section shall have a minimum contrast of 60%</li> </ul>	
<b>Test</b>	AS.NZS 1428.4.1 2009 Appendix E (pg 70-77)
<b>Rating</b>	R12